

CH4 Methane Sensor

MST-N4L CH₄ Datasheet



Application

- ◆ Environmental detection
- ◆ Gas leakage detection
- ◆ On-line monitoring

Advantages& characteristics

- ◆ Quick response and accurate measurement
- ◆ Will not get poisoned
- ◆ Working with no oxygen required
- ◆ More than 5 years lifespan
- ◆ Small size structure

Base Specification

◆ Detection gas	CH ₄
◆ Working principle	Non-distributed infrared (NDIR)
◆ Measuring range	0-10000ppm, 0-100%LEL, 0-5%/10%/20%/100%vol
◆ Accuracy	0-10000ppm: ±3%FS LEL/vol: ±(1%FS+3%Truth value)
◆ Resolution	1ppm / 1%LEL / 0.01vol
◆ Response time (T90)	<30s (Free diffusion)
◆ Working temperature	-40℃ ~ 70℃
◆ Storage temperature	-40℃ ~ 85℃
◆ Working humidity	0 ~ 95%RH, non-condensing
◆ Preheating time	1min
◆ Digital output	TTL level
◆ Analog output	0.4 ~ 2V
◆ Supply voltage	3.0 ~ 5.5 VDC
◆ Working current	Average <60mA @ 3.3VDC
◆ Power consumption	0.2W (Average value)
◆ Lifespan	>5 years
◆ Warranty	1 year
◆ Weight	21g

Pin specification

Pin mark	Function	Description
V+	Positive electrode of power supply	3.0 - 5.5 VDC
Gnd	Negative terminal of power supply	GND
Tx	Serial port transmitter	TTL TXD
Rx	Serial port receiver	TTL RXD
DA	Analog output	0V means sensor failure 0.2V means sensor in preheating 0.4-2V corresponds to 0-100% F.S. 2-2.2V means overrange

Size drawing (unit: mm)

