

## C5H10 Cyclopentane Sensor

# MST-N4L C5H10 Datasheet



### Application

- ◆ Environmental detection
- ◆ Gas leakage detection
- ◆ On-line monitoring

### Advantages& characteristics

- ◆ Quick response and accurate measurement
- ◆ Will not get poisoned
- ◆ Working with no oxygen required
- ◆ More than 5 years lifespan
- ◆ Small size structure

### Base Specification

- ◆ Detection gas C5H10 Cyclopentane
- ◆ Working principle Non-distributed infrared (NDIR)
- ◆ Measuring range 0-1%VOL
- ◆ Accuracy  $\pm 3\%$ FS
- ◆ Resolution 0.01%VOL
- ◆ Response time (T90) <30s (Free diffusion)
- ◆ Working temperature  $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$
- ◆ Storage temperature  $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
- ◆ Working humidity 0 ~ 95%RH, non-condensing
- ◆ Preheating time 1min
- ◆ Digital output TTL level
- ◆ Analog output 0.4 ~ 2V
- ◆ Supply voltage 3.0 ~ 5.5 VDC
- ◆ Working current Average <60mA @ 3.3VDC
- ◆ Power consumption 0.2W (Average value)
- ◆ Lifespan >5 years
- ◆ Warranty 1 year
- ◆ Weight 21g

### Pin specification

Pin mark	Function	Description
V+	Positive electrode of power supply	3.0 - 5.5 VDC
Gnd	Negative terminal of power supply	GND
Tx	Serial port transmitter	TTL TXD
Rx	Serial port receiver	TTL RXD
DA	Analog output	0V means sensor failure 0.2V means sensor in preheating 0.4-2V corresponds to 0-100% F.S. 2-2.2V means overrange

### Size drawing (unit: mm)

